

XS15

SURFACE




MONOLINE-XS15

A surface mounted extruded aluminium profile manufactured from high-density aluminium, with a highly durable anodised finish. Available with frosted or opal diffusers.


MONOFLEX LED available in static white, tunable white and dynamic colour changing, with a choice of Nichia, Osram or Lumileds LED.

TECHNICAL

Housing:	Anodised Aluminium
Diffuser:	Polycarbonate UV Stabilised
Lengths:	2000mm & 3000mm
Max LED Wattage:	24w/m
Max PCB Width:	12mm
Hot-Spot Free:	≥112 LED/m
Weight:	0.19kg/m
IP Rating:	IP40



FINISH




CATALOGUE NO.

XS15-2-FC	2000mm anodised silver with frosted diffuser
XS15-2-OC	2000mm anodised silver with opal diffuser
XS15-3-FC	3000mm anodised silver with frosted diffuser
XS15-3-OC	3000mm anodised silver with opal diffuser

ACCESSORIES



XS15-SMB Sprung steel bracket



XS15-MAG Sprung steel magnetic bracket



XS15-EC Aluminium end cap



XS15-ECH Aluminium end cap with hole

XS15

SURFACE

PRODUCT CODE EXAMPLE

PROFILE		DIFFUSER		PCB		WATTAGE		SPECTRUM		LENGTH
XS15	-	OC	-	D112	/	9	-	D3-827	-	L4

SPECIFICATION

Profile	Diffuser	PCB	Wattage	Spectrum	Standard Lengths
	- CC Clear - FC Frosted - OC Opal	- D112 - N112	4 4.8w/m 9 9.6w/m 14 14.4w/m 19 19.2w/m 24 24.0w/m	- D3-827 Osram 2700K ≥Ra80 - D3-927 Lumileds 2700K ≥Ra90 - D3-830 Osram 3000K ≥Ra80 - D3-930 Lumileds 3000K ≥Ra90 - D3-835 Osram 3500K ≥Ra80 - D3-935 Lumileds 3500K ≥Ra90 - D3-840 Osram 4000K ≥Ra80 - D3-940 Lumileds 4000K ≥Ra90 - D3-850 Osram 5000K ≥Ra80 - D3-950 Lumileds 5000K ≥Ra90 - D3-857 Osram 5700K ≥Ra80 - D3-957 Lumileds 5700K ≥Ra90 - D3-865 Osram 6500K ≥Ra80 - D3-965 Lumileds 6500K ≥Ra90 - N3-820 Nichia 4000K ≥Ra90 - N3-920 Nichia 4000K ≥Ra90 - N3-822 Nichia 2200K ≥Ra80 - N3-922 Nichia 2200K ≥Ra90 - N3-825 Nichia 2500K ≥Ra80 - N3-925 Nichia 2500K ≥Ra90 - N3-827 Nichia 2700K ≥Ra80 - N3-927 Nichia 2700K ≥Ra90 - N3-830 Nichia 3000K ≥Ra80 - N3-930 Nichia 3000K ≥Ra90 - N3-835 Nichia 3500K ≥Ra80 - N3-935 Nichia 3500K ≥Ra90 - N3-840 Nichia 4000K ≥Ra80 - N3-940 Nichia 4000K ≥Ra90 - N3-850 Nichia 5000K ≥Ra80 - N3-950 Nichia 5000K ≥Ra90 - N3-857 Nichia 5700K ≥Ra80 - N3-957 Nichia 5700K ≥Ra90 - N3-865 Nichia 6500K ≥Ra80 - N3-965 Nichia 6500K ≥Ra90	- L1 450mm - L2 950mm - L3 1450mm - L4 1950mm - L5 2450mm - L6 2950mm Cutttable at 62.5mm intervals

Other colour temperatures, tunable white, RGB and RGBW available upon request.

ACCESSORIES

Disclaimer:
 Technical data is subject to change without prior notice. The data provide represent typical values. Due to tolerances in the production of components and binning of LEDs, values for lumen output (Lm), colour temperature (CCT) and power (W/m) can vary up to 10%. Electrical and thermal variation also influences the performance characteristics of LEDs