


XS20

SURFACE



MONOLINE-XS20

A miniature surface mounted linear LED luminaire manufactured from extruded anodised aluminium, with opal polycarbonate diffusers. Suitable for surface mounting via concealed plastic mounting base or magnetic fixings. Can also be pendant mounted using the suspension mounting kit.

Each PCB module has an on-board Integrated Controller (IC), for precise constant current control, whilst a Schottky diode provides reverse polarity protection.

A range of LED options are available with a choice of Nichia, Osram or Lumileds LED, with colour temperatures from 2000K - 6500K and power outputs from 4.8W/m - 24.0W/m.



Available in four standard lengths: 450mm, 950mm, 1450mm & 1950mm, which can be cut at 62.5mm intervals. Custom sizes also available upon request.



TECHNICAL

Input voltage:	24VDC [22.5~25VDC]
Current control:	On-board integrated controller (IC)
Reverse voltage protection:	On-board Schottky diode
Operating temperature (Ta):	-35 °C ~ 50 °C
PCB Temperature (Tc max):	<75 °C
Dimmable:	PWM (0/1-10V, DALI, DMX, TRIAC, ELV)
Ingress protection:	IP40

FINISH



XS20

SURFACE




PRODUCT CODE EXAMPLE

PROFILE		DIFFUSER		PCB		WATTAGE		SPECTRUM		LENGTH
XS20	-	OC	-	D112	/	9	-	D4-827	-	L4


SPECIFICATION

Profile	Diffuser	PCB	Wattage	Spectrum	Standard Lengths
	OC Opal	D112	4 4.8w/m 9 9.6w/m 14 14.4w/m 19 19.2w/m 24 24.0w/m	D4-827 Osram 2700K ≥Ra80 D4-927 Lumileds 2700K ≥Ra90 D4-830 Osram 3000K ≥Ra80 D4-930 Lumileds 3000K ≥Ra90 D4-835 Osram 3500K ≥Ra80 D4-935 Lumileds 3500K ≥Ra90 D4-840 Osram 4000K ≥Ra80 D4-940 Lumileds 4000K ≥Ra90 D4-850 Osram 5000K ≥Ra80 D4-950 Lumileds 5000K ≥Ra90 D4-857 Osram 5700K ≥Ra80 D4-957 Lumileds 5700K ≥Ra90 D4-865 Osram 6500K ≥Ra80 D4-965 Lumileds 6500K ≥Ra90	L1 450mm L2 950mm L3 1450mm L4 1950mm Cutttable at 62.5mm intervals
		N112	4 4.8w/m 9 9.6w/m 14 14.4w/m 19 19.2w/m 24 24.0w/m	N4-820 Nichia 4000K ≥Ra80 N4-920 Nichia 4000K ≥Ra90 N4-822 Nichia 2200K ≥Ra80 N4-922 Nichia 2200K ≥Ra90 N4-825 Nichia 2500K ≥Ra80 N4-925 Nichia 2500K ≥Ra90 N4-827 Nichia 2700K ≥Ra80 N4-927 Nichia 2700K ≥Ra90 N4-830 Nichia 3000K ≥Ra80 N4-930 Nichia 3000K ≥Ra90 N4-835 Nichia 3500K ≥Ra80 N4-935 Nichia 3500K ≥Ra90 N4-840 Nichia 4000K ≥Ra80 N4-940 Nichia 4000K ≥Ra90 N4-850 Nichia 5000K ≥Ra80 N4-950 Nichia 5000K ≥Ra90 N4-857 Nichia 5700K ≥Ra80 N4-957 Nichia 5700K ≥Ra90 N4-865 Nichia 6500K ≥Ra80 N4-965 Nichia 6500K ≥Ra90	
Other colour temperatures, tunable white, RGB and RGBW available upon request.					

ACCESSORIES



XS20-LC Connector every 3 metres



XS20-LC90 90° connector every corner



XS20-EC Aluminium End Cap

Disclaimer:

Technical data is subject to change without prior notice. The data provide represent typical values. Due to tolerances in the production of components and binning of LEDs, values for lumen output (Lm), colour temperature (CCT) and power (W/m) can vary up to 10%. Electrical and thermal variation also influences the performance characteristics of LEDs