





## MONOLINE-XS3

A surface mounted extruded aluminium profile manufactured from high-density aluminium, with a highly durable anodised finish and opal (OC) diffuser.


MONOFLEX LED available in static white, tunable white and dynamic colour changing, with a choice of Nichia, Osram or Lumileds LED.

## TECHNICAL

|                         |                             |
|-------------------------|-----------------------------|
| <b>Housing:</b>         | Anodised Aluminium          |
| <b>Diffuser:</b>        | Polycarbonate UV Stabilised |
| <b>Lengths:</b>         | 2000mm & 3000mm             |
| <b>Max LED Wattage:</b> | 14.4w/m                     |
| <b>Max PCB Width:</b>   | 6mm                         |
| <b>Hot-Spot Free:</b>   | ≥112 LED/m                  |
| <b>Weight:</b>          | 0.12kg/m                    |
| <b>IP Rating:</b>       | IP40                        |



## FINISH



## CATALOGUE NO.

|                 |                                           |
|-----------------|-------------------------------------------|
| <b>XS3-2-OC</b> | 2000mm anodised silver with opal diffuser |
| <b>XS3-3-OC</b> | 3000mm anodised silver with opal diffuser |

## ACCESSORIES



XS3-EC Aluminium end cap



XS3-ECH Aluminium end cap with hole