




MONOLINE-XS7

A surface mounted extruded aluminium profile manufactured from high-density aluminium, with a highly durable anodised finish. Available with frosted or opal diffuser.


MONOFLEX LED available in static white, tunable white and dynamic colour changing, with a choice of Nichia, Osram or Lumileds LED.

TECHNICAL

Housing:	Anodised Aluminium
Diffuser:	Polycarbonate UV Stabilised
Lengths:	2000mm & 3000mm
Max LED Wattage:	19.2w/m
Max PCB Width:	12mm
Hot-Spot Free:	≥112 LED/m
Weight:	0.12kg/m
IP Rating:	IP40



FINISH



CATALOGUE NO.

XS7-2-CC	2000mm anodised silver with clear cover
XS7-2-FC	2000mm anodised silver with frosted diffuser
XS7-2-OC	2000mm anodised silver with opal diffuser
XS7-3-CC	3000mm anodised silver with clear cover
XS7-3-FC	3000mm anodised silver with frosted diffuser
XS7-3-OC	3000mm anodised silver with opal diffuser

ACCESSORIES



XS7-SMB Sprung steel bracket



XS7-MAG Sprung steel magnetic bracket



XS7-EC Aluminium end cap



XS7-ECH Aluminium end cap with hole