



RF 110, led cob 12-17w | CRI 95



2 nero
 black

4 bianco
 white

Apparecchio ad incasso trimless a LED, completo di alimentatore e connessioni, tolleranza colore 3 McAdams, vita operativa 50.000 ore, gradi di emissione 16° (spot) oppure 38° (flood), non orientabile.
Trimless recessed LED fixture, complete with driver and connections, colour tolerance 3 McAdams, working life 50.000 hours, emission degrees 16° (spot) or 38° (flood), not orientable.

18.2008.01.16.-- 2 4
12w, 3000°K, 1500lm, 125lm/w, CRI 95,



18.2008.01.32.-- 2 4
12w, 3000°K, 1500lm, 125lm/w, CRI 95,



18.2008.02.16.-- 2 4
17w, 3000°K, 2070lm, 122lm/w, CRI 95,



18.2008.02.32.-- 2 4
17w, 3000°K, 2070lm, 122lm/w, CRI 95,



cod. 18.2008.**.2700.(X°).-- per 2700°K
cod. 18.2008.**.4000.(X°).-- per 4000°K

RF_110, 21W DALI

18.2008.08.(°K).(X°).--
17w, 2070lm, 122lm/w, CRI 95, 500mA,

RF_110, led without driver
Driver da aggiungere separatamente.
Drivers to be added separately.



18.2008.03.(°K).(X°).-- 2 4
Max 17w, CRI 95, max 500mA,



plaster kit / kit da stuccare

18.2008.PK plaster kit